



**Main**

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Distribution length
BAR MATERIAL	Aluminium
Device application	Medium power distribution
[Ie] rated operational current	100 A at 35 °C
Number of tap-off outlets	12

**Complementary**

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uiimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	2.6 kA
[Ipk] rated peak withstand current	15.7 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.22 µT
Thermal stress limit	6.8 kA <sup>2</sup> .s
THDI	0...15 % 100 A 15...33 % 80 A 33...100 % 63 A
Maximum voltage drop	<0.138 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.13 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.118 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.106 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + N + PE
Dimension type	Fix
Width	146 mm
Depth	54 mm
Length	3 m
Net weight	12.1 kg

**Environment**

Standards	IEC 61439-6 IEC 60439-2
-----------	----------------------------

**Packing Units**

Package 1 Weight	12.100 kg
Package 1 Height	1.600 dm
Package 1 width	0.640 dm
Package 1 Length	30.900 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

