



Main

| | |
|---------------------------|-----------------|
| Range of product | Canalis |
| Product or component type | Busbar trunking |
| Product compatibility | KBB |

Complementary

| | |
|--|--|
| Device application | Lighting Power socket distribution |
| Maximum radiated magnetic field | 2 pT |
| [Ue] rated operational voltage | 230...400 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| [Ui] rated insulation voltage | 690 V |
| [Ie] rated operational current | 25 A at 35 °C |
| Network frequency | 50/60 Hz |
| [Icw] rated short-time withstand current | 0.44 kA |
| [Ipk] rated peak withstand current | 4.4 kA |
| Thermal stress limit | 195 kA ² .s |
| THDI | 0...15 % 25 A 15...33 % 20 A 33...100 % 16 A |
| Maximum voltage drop | <0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.67 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.61 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.55 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode | By screws |
| Busbar description | Straight length |
| Busbar trunking polarity | L + N + PE |
| Number of circuits | 2 |
| Number of tap-off outlets | 5 |
| Control type | Without |
| Standards | EN/IEC 61439-6 EN/IEC 60439-2 |
| Width | 3100 mm |
| Depth | 51 mm |
| Height | 60 mm |
| Length | 3 m |
| Colour | White (RAL 9003) |
| Net weight | 4.6 kg |
| Quantity per set | Set of 6 |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP55 conforming to EN/IEC 60529 |
| IK degree of protection | IK06 conforming to EN/IEC 62262 |
| Ambient air temperature for operation | 0...35 °C (100 % of In) 35...40 °C (96 % of In) 40...45 °C (93 % of In) 45...50 °C (89 % of In) 50...55 °C (85 % of In) |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 4.7 kg |
| Package 1 Height | 5.1 cm |
| Package 1 width | 6 cm |
| Package 1 Length | 310 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 30 kg |
| Package 2 Height | 13 cm |
| Package 2 width | 16 cm |
| Package 2 Length | 315 cm |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 72 |
| Package 3 Weight | 363 kg |
| Package 3 Height | 51 cm |
| Package 3 width | 65 cm |
| Package 3 Length | 320 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

