

# Product data sheet

## Characteristics

# KBC16DCB226

Canalis - tap-off unit - 16A - fixed polarity  
without protection - blue



### Main

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBB KBA
Device application	Lighting

### Complementary

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L2 + N2 + L3 + N3 + PE
Tap-off unit polarity	L2 + N + PE
Tap-off unit connector type	With fixed polarity
Tap-off lock colour	Blue
Standards	EN/IEC 61439-6 EN/IEC 60439-2
Width	168 mm
Depth	33 mm
Height	53 mm
Colour	Light grey (RAL 7035)
Net weight	90 g
Quantity per set	Set of 10

### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	120 g
Package 1 Height	5.5 cm
Package 1 width	6.5 cm
Package 1 Length	14 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	3.2 kg
Package 2 Height	12 cm
Package 2 width	16 cm

Package 2 Length	25 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	280
Package 3 Weight	41.7 kg
Package 3 Height	62 cm
Package 3 width	85 cm
Package 3 Length	92 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------

