



Main

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBB KBA
Device application	Lighting
Range compatibility	KBA busbar trunking KBB busbar trunking

Complementary

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L2 + L1 + L3 + PE
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	205 mm
Depth	38 mm
Height	68 mm
Colour	Cream (RAL 9001)
Net weight	90 g

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	189 g
Package 1 Height	8 cm
Package 1 width	8 cm
Package 1 Length	18 cm
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	3.899 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06

Number of Units in Package 3	144
Package 3 Weight	40.62 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

