



**Main**

Range of product	Canalis
Range compatibility	KS busbar trunking
Offer type	Rising main
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunking plug-in
[Ie] rated operational current	250 A at 35 °C
Protection type	Circuit breaker: NSX250
Provided equipment	Circuit breaker to be ordered separately 2 DIN rail
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

**Complementary**

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	400 V depending on protective device 500 V depending on protective device 690 V depending on protective device
Network frequency	50/60 Hz
Control type	Rotary handle
Electrical connection	Crimp lug - ISO32 70 mm <sup>2</sup> flexible Crimp lug - ISO32 150 mm <sup>2</sup> rigid
Door/cover opening side	Right
Tap-off unit disconnection mode	By opening the door
Number of openings	1 opening for FL21 gland plate
Standards	IEC 61439-6 IEC 61439-1
Body material	Metal
18 mm pitches	25
Width	432 mm
Depth	405 mm
Height	632 mm
Net weight	13.5 kg

**Environment**

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	16.8 kg
Package 1 Height	44 cm
Package 1 width	33 cm
Package 1 Length	65 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

