



Main

Range of product	Canalis
Range compatibility	KS busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunking plug-in
[Ie] rated operational current	400 A at 35 °C
Protection type	Fuse isolator: Efen fuse, size 2 conforming to DIN
Provided equipment	Fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
[Uimp] rated impulse withstand voltage	6.8 kV
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO63 240 mm <sup>2</sup> flexible Cable clamp terminal - ISO63 240 mm <sup>2</sup> rigid
Door/cover opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Body material	Metal
Width	587 mm
Depth	120 mm
Depth (door open)	763 mm
Height	350 mm
Net weight	9 kg

Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	9 kg
Package 1 Height	12 cm
Package 1 width	34.8 cm
Package 1 Length	57.3 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

