



### Main

Range of product	Canalis
Range compatibility	KS busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunkingplug-in
[I <sub>e</sub> ] rated operational current	32 A at 35 °C
Protection type	Fuse isolator: for gG cylindrical fuse, size 10 x 38 mm - 25 A conforming to NF Fuse isolator: for aM cylindrical fuse, size 10 x 38 mm - 32 A conforming to NF
Provided equipment	Fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

### Complementary

Device application	Medium power distribution
[U <sub>e</sub> ] rated operational voltage	230...690 V depending on protective device
[U <sub>imp</sub> ] rated impulse withstand voltage	6.8 kV
[U <sub>i</sub> ] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO32 6 mm <sup>2</sup> flexible Cable clamp terminal - ISO32 10 mm <sup>2</sup> rigid
Door/cover opening side	Front
Tap-off unit disconnection mode	By drawing out
Standards	IEC 61439-1 IEC 61439-6
Body material	Plastic
Width	135 mm
Depth	153 mm
Height	175 mm
Net weight	0.6 kg

### Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	645 g
Package 1 Height	15.5 cm
Package 1 width	16.8 cm
Package 1 Length	18.3 cm
Unit Type of Package 2	P12

Number of Units in Package 2	119
Package 2 Weight	89.24 kg
Package 2 Height	79 cm
Package 2 width	80 cm
Package 2 Length	120 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------

