



Main

Range of product	Canalis
Product name	KS
Product or component type	Tap-off unit
Protection type	Surge arrester
Tap-off unit polarity	3L+N+PE
Provided equipment	Quick PRD40r 3P+N
Surge arrester class type	Type 2

Complementary

[Ue] rated operational voltage	230...415 V
Network frequency	50/60 Hz
[Ics] rated service breaking capacity	25 kA
Maximum discharge current	40 kA
Electrical connection	Pre-cabled
Tap-off unit disconnection mode	By opening the tap-off unit cover
Tap-off unit connector type	With fixed polarity
Door opening side	Right
Door opening size	432.5 mm
Standards	IEC 60439-2 IEC 81643-1 EN 61643-11
Body material	Plastic
Colour	White (RAL 9001)
Width	357 mm
Depth	108 mm
Height	202 mm
Net weight	3.4 kg

Environment

Earthing system	TT TN-C TN-S
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.5 kg
Package 1 Height	15.8 cm
Package 1 width	20.2 cm
Package 1 Length	35.7 cm
Unit Type of Package 2	P12

Number of Units in Package 2	38
Package 2 Weight	133 kg
Package 2 Height	195 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

