



Main

Range of product	Canalis
Product name	KS
Product or component type	Adapter
Product compatibility	KS
[Ie] rated operational current	250 A
Offer type	Spare part
Colour	White (RAL 9001)

Complementary

Accessory / separate part category	Adaptation
Device application	Adapt old offer
Mounting location	Between trunking
Mounting mode	By screws
Mounting support	Busbar
Busbar trunking polarity	3L + N + PE
Width	211 mm
Depth	74 mm
Height	184.5 mm
Body material	Plastic
Net weight	1.6 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
Standards	IEC 60439-2 IEC 61439-6

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.796 kg
Package 1 Height	12 cm
Package 1 width	19.5 cm
Package 1 Length	22.5 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Weight	183 kg
Package 2 Height	62 cm
Package 2 width	75 cm
Package 2 Length	92 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

