



Main

Range of product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector M23, 19 pins
Collar material	Metal
Status LED	Without
Cable connection	Solder terminal / wire size <1 mm ² / clamping capacity 9...12 mm

Complementary

Cable gland type	Pg 13.5
Cable connector fixing	Screw-on
[Ue] rated operational voltage	60 V AC 75 V DC
[In] rated current	7.5 A
Enclosure material	Metal
Minimum insulating resistance	10000000 GΩ
Contact resistance	5000 μOhm
Net weight	0.15 kg

Environment

IP degree of protection	IP65
Ambient air temperature for operation	-25...110 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	147 g
Package 1 Height	3 cm
Package 1 width	7 cm
Package 1 Length	9 cm
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Weight	3.498 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm


Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



(1) Cable gland: no. 13 metal (Pg 13.5)

Connections and Schemes

