

XZCR1111064D3

Telemecanique Safety light curtains XUSL,
Series connection jumper, 2 straight M12,
Female/Female con, 3 m, 5 pins



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part type	Jumper cable
Accessory / separate part category	Connection accessory
Accessory / separate part destination	Safety light curtain master/slave XCSR RFID safety switch

Complementary

Product compatibility	XUSL2 XUSL4 XC SRC.2M12
Connector type	M12 female 5 pins straight
Wire insulation material	PUR
Collar material	Nickel plated brass
Cable outer diameter	5 mm
Cable composition	5 x 0.34 mm ²
Cable length	3 m

Environment

IP degree of protection	IP65 IP67 IP69K
-------------------------	-----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	134 g
Package 1 Height	2 cm
Package 1 width	18 cm
Package 1 Length	18 cm
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Weight	4.36 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes