



## Main

|                                    |                                  |
|------------------------------------|----------------------------------|
| Range of product                   | Telemecanique Cabling components |
| Accessory / separate part category | Cabling accessory                |
| Accessory / separate part type     | Pre-wired connectors             |

## Complementary

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| Electrical connection          | Elbowed female connector M12, 5 pins (included earth pin) |
| Cable connector fixing         | Screw-on                                                  |
| Collar material                | Metal                                                     |
| Status LED                     | Without                                                   |
| Cable length                   | 15 m                                                      |
| Cable outer diameter           | 5.9 mm                                                    |
| Cable composition              | 5 x 0.34 mm <sup>2</sup>                                  |
| Wire insulation material       | PUR                                                       |
| [Ue] rated operational voltage | 30 V AC<br>36 V DC                                        |
| [In] rated current             | 4 A                                                       |
| Contact resistance             | 5000 µOhm                                                 |
| Minimum insulating resistance  | 1 GΩ                                                      |

## Environment

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| IP degree of protection               | IP65<br>IP69K<br>IP67                    |
| Product certifications                | CULus                                    |
| Ambient air temperature for operation | -40...80 °C static<br>-5...80 °C flexing |
| Ambient air temperature for storage   | -40...80 °C                              |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 520 g    |
| Package 1 Height             | 5.2 cm   |
| Package 1 width              | 18.6 cm  |
| Package 1 Length             | 20.4 cm  |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 7        |
| Package 2 Weight             | 4.207 kg |
| Package 2 Height             | 15 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |