



Main

Range of product	AccuSine
Product name	AccuSine PFV+
Product or component type	Electronic VAR controller

Complementary

Network type	3P
Network configuration	3 or 4 wires
Network rated voltage	380...480 V AC
Network frequency	50/60 Hz +/- 3 % auto-sensing
Maximum permissible voltage	1.1 x Un
RMS output current rating	120 A
Reactive power rating	100 kvar 480 V AC 50/60 Hz
Operating mode	Power factor correction Volt-var support Mains current balancing
Installation location	Indoor
Enclosure mounting	Wall mounted
Protection type	Without protection
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Conducted EMC, class A conforming to EN 61000-6-4
Accessibility for operation	Front
Location of connection	Bottom

Environment

Enclosure degree of protection	IP00
Environmental characteristic	Operating: 3C2 conforming to IEC 60721-3-3 Operating: 3S2 conforming to IEC 60721-3-3 Storage: 3C3 conforming to IEC 60721-3-3 Storage: 3S3 conforming to IEC 60721-3-3
Operating altitude	<= 1000 m 1 % per 100 m
Ambient air temperature for operation	0...40 °C 0...50 °C maximum with current derating of 2 % per °C
Relative humidity	0...95 %
PCBA protection	Conformal coated
Standards	CSA C22.2 No 60947-1-07 UL 508 EN 61000-6-4 UL 60947-1 CSA C22.2 No 14 EN 60439-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product certifications	CULus DNV-GL CE ABS RCM
Ambient air temperature for storage	-20...60 °C
Net weight	110 kg
Height	1400 mm
Width	421 mm
Depth	384 mm
Colour	Light grey (RAL 7035)

Packing Units

Package 1 Weight	167.000 kg
Package 1 Height	0.705 m
Package 1 width	0.737 m
Package 1 Length	1.733 m

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------