# EVCP200D5IP31

Electronic VAR control - 200 A 380..480 V AC - IP31 enclosure





#### Main

Range of product	AccuSine
Product name	AccuSine PFV+
Product or component type	Electronic VAR controller

#### Complementary

o in promortiary	
Network type	3P
Network configuration	3 or 4 wires
Network rated voltage	380480 V AC
Network frequency	50/60 Hz +/- 3 % auto-sensing
Maximum permissible voltage	1.1 x Un
RMS output current rating	200 A
Reactive power rating	166 kvar 480 V AC 50/60 Hz
Operating mode	Volt-var support Power factor correction Mains current balancing
Installation location	Indoor
Enclosure mounting	Floor-standing
Protection type	Circuit breaker protection
Disconnect type	Door-interlocked with rotary handle
Interrupt capacity	200 kA
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Conducted EMC, class A conforming to EN 61000-6-4
Accessibility for operation	Front
Location of connection	Top or bottom

#### Environment

Enclosure degree of protection	IP31
Environmental characteristic	Operating: 3C2 conforming to IEC 60721-3-3 Operating: 3S2 conforming to IEC 60721-3-3 Storage: 3C3 conforming to IEC 60721-3-3 Storage: 3S3 conforming to IEC 60721-3-3
Operating altitude	<= 1000 m 1 % per 100 m
Ambient air temperature for operation	040 °C 050 °C maximum with current derating of 2 % per °C
Relative humidity	095 %
PCBA protection	Conformal coated
Standards	EN 61000-6-4 UL 60947-1 EN 60439-1 CSA C22.2 No 14 UL 508 CSA C22.2 No 60947-1-07

Product certifications	CULus CE RCM
Ambient air temperature for storage	ABS -2060 °C
Net weight	355 kg
Height	2100 mm
Width	900 mm
Depth	600 mm
Colour	Light grey (RAL 7035)

# Packing Units

Package 1 Weight	475.000 kg	
Package 1 Height	2.331 m	
Package 1 width	1.194 m	
Package 1 Length	1.194 m	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☐ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

## Contractual warranty

Warranty	18 months
----------	-----------