



### Main

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Range                     | Masterpact                                                         |
| Product or component type | Ethernet interface module                                          |
| Device application        | Communication                                                      |
| Range compatibility       | Masterpact MTZ2 circuit breaker<br>Masterpact MTZ3 circuit breaker |
| Device mounting           | Embedded                                                           |





### Complementary



|                            |                                                                     |
|----------------------------|---------------------------------------------------------------------|
| Communication gateway      | Ethernet TCP/IP to Modbus                                           |
| Communication network type | ULP, CANopen on USB<br>Ethernet, Ethernet TCP/IP10/100 Mbps on RJ45 |
| Mounting mode              | Drawout                                                             |
| Mounting support           | DIN rail                                                            |
| Localisation on device     | Chassis                                                             |
| Maximum supply current     | 3 A                                                                 |
| Power consumption in W     | 72 W                                                                |
| Product certifications     | EAC<br>CE<br>FCC                                                    |
| Standards                  | IEC 60947-6-2<br>IACS E10<br>IEC 60950                              |
| Height                     | 51 mm                                                               |
| Width                      | 51 mm                                                               |
| Depth                      | 52.5 mm                                                             |
| Net weight                 | 0.075 kg                                                            |
| Web server                 | Embedded                                                            |
| Provided equipment         | 1 instruction sheet                                                 |
| Offer type                 | Spare part                                                          |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| IP degree of protection               | IP30        |
| Ambient air temperature for operation | -20...70 °C |

### Offer Sustainability

|                            |                                                                                                                   |
|----------------------------|-------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                             |
| REACH Regulation           |  REACH Declaration             |
| EU RoHS Directive          | Compliant  EU RoHS Declaration |
| Mercury free               | Yes                                                                                                               |
| RoHS exemption information |  Yes                           |
| China RoHS Regulation      |  China RoHS Declaration        |

|                             |                                                                                                                                |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Environmental Disclosure    |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile         |  <a href="#">End Of Life Information</a>      |
| Halogen content performance | Halogen free plastic parts product                                                                                             |
| <b>Contractual warranty</b> |                                                                                                                                |
| Warranty                    | 18 months                                                                                                                      |