

XIOT11SERMRCL

Wireless transmitter, Dry contact LPWAN
Online subscription



Main

[Us] rated supply voltage	3.6 V nominal
Battery type	Lithium integrated
Battery life	13.6 Year(S) 2 frames/day 4.2 Year(S) 10 frames/day 2.3 year(s) 20 frames/day
Number of inputs	4 dry contact
Electrical connection	Cable 2 m
Range of product	Telemecanique Cloud connected sensor XIOT
Product or component type	Wireless transmitter
Web services	Smartphone app Web server
Device application	Connection to SCADA
Type of license	Online client
Communication network type	Sigfox Europe
Transmission trigger	On change on one of the inputs 1 status frame per day
Max transmission frequency	6 frames/h 50 frames/day
Transmission rate	100 bit/s
Fixing mode	By screws
Height	100 mm
Length	45 mm
Width	50 mm
Net weight	0.216 kg
Radio frequency fields	868 MHz
Radio power	14 dBm
Operating distance	<= 10000 m

Complementary

Product destination	Pressure switch XMLA Pressure switch XMLB Pressure switch XMLC Pressure switch XMLD Limit switch XCM Limit switch XCKM Limit switch XCKL Limit switch XCKS Limit switch XCKJ Limit switch XCKN Limit switch XCKP Limit switch XCKT Limit switch XCKD
---------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. This information is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Directives	1999/5/EC - R&TTE directive
Product certifications	CE Sigfox ready
Standards	EN 62368-1 EN 301-489-1 ETSI EN 300 220-2
Ambient air temperature for operation	-25...70 °C
IP degree of protection	IP66

Packing Units

Package 1 Weight	0.215 kg
Package 1 Height	0.470 dm
Package 1 width	1.240 dm
Package 1 Length	2.080 dm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins