

Product data sheet

Characteristics

TCSMCN1F2

Radio frequency identification XG, Modbus shielded cable, M12 female connector, end with free wires, IP67, 2 m



Main

Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	Modbus shielded pre-wired M12 connector
Accessory / separate part destination	Modbus/Uni-Telway network Tap-off box
Cable length	2 m

Complementary

Product compatibility	TCSAMT31FP TSXSAC50
Electrical connection	1 female connector M12 straight A coding Bare wires
Colour	Black
Net weight	0.115 kg

Environment

IP degree of protection	IP67
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	137 g
Package 1 Height	2 cm
Package 1 width	18.5 cm
Package 1 Length	18.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	16
Package 2 Weight	2.62 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability


REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Wiring Diagram

Modbus Connections



Pin no.		Signal
1	-	Drain (Modbus-SHLD)
2	Red	+ 24 VDC
3	Black	0 V/Modbus-GND
4	White	D0
5	Blue	D1
Connector casing		Shielding