



Main

Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part destination	XGSD XGSK XGCS
Product or component type	RS232/RS485 interface
Accessory / separate part type	RS232C/RS485 line adaptor

Complementary

Communication port converter	RS232C/RS485 no modem signals
Connection element	RS232/RS485 interface
Current consumption	20 mA
[Ie] rated operational current DC	20 mA
Mounting support	35 mm symmetrical DIN rail
Product mounting	35 mm symmetrical DIN rail
Net weight	0.105 Kg 0.1 kg
[Us] rated supply voltage	18...30 V DC 24 V DC
Supply voltage limits	20...30 V
Transmission rate	<= 19200 bit/s 19200 bauds
Electrical connection	Screw connectors

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	109 g
Package 1 Height	5 cm
Package 1 width	6.5 cm
Package 1 Length	13 cm
Unit Type of Package 2	S02
Number of Units in Package 2	28
Package 2 Weight	3.422 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------