

# XGHB320246

Electronic tag, Radio frequency identification  
XG, RFID 13.56 MHz, disc Ø 30 x 3, 2000  
Bytes



## Main

Range of product	Telemecanique Radio frequency identification XG
Product or component type	Electronic tag
RFID electronic tag name	XGHB
RFID frequency	13.56 MHz
Design	Disc
Memory capacity	2 kB
Associated smart antenna	XGCS
[Sn] nominal sensing distance	42 Mm with XGCS49 + field expander XGFEC540 48 Mm with XGCS49 65 Mm with XGCS89 80 Mm with XGCS49 + field expander XGFEC2525 65 mm with XGCS85
Outer dimension	Ø 30 x 3 mm
Quantity per set	Set of 5
Read time	7 + 2 x (number of 16-bit words) ms
Write time	7 + 2.4 x (number of 16-bit words) ms
IP degree of protection	IP68
Fixing mode	By screws

## Complementary

Memory type	FeRAM
Memory operation	Read/write
Number of read cycles	1000000000
Number of write cycles	1000000000 at -25...70 °C
Maximum linear speed with "auto read/write function"	2.1 M/S with XGCS49 (read a serial number) 1.5 M/S with XGCS49 (read a word) 0.6 M/S with XGCS49 (read or write 10 words) 3.5 M/S with XGCS89 (read a serial number) 2.5 M/S with XGCS89 (read a word) 1 M/S with XGCS89 (read or write 10 words) 3.5 M/S with XGCS85 (read a serial number) 2.5 M/S with XGCS85 (read a word) 1 m/s with XGCS85 (read or write 10 words)
Data retention time	10 year(s)
Material	PPA (polyphthalamide)
Net weight	0.005 kg

## Environment

Standards	ISO 15693
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Vibration resistance	2 mm conforming to EN 60068-2-6 (f = 5...29.5 Hz) 7 gn conforming to EN 60068-2-6 (f = 29.5...150 Hz)
Shock resistance	30 gn conforming to EN 60068-2-27 for 11 ms
IK degree of protection	IK02 conforming to EN 50102

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3 g
Package 1 Height	1 cm
Package 1 width	6 cm
Package 1 Length	9 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	5
Package 2 Weight	18 g
Package 2 Height	14 cm
Package 2 width	8 cm
Package 2 Length	1 cm
Unit Type of Package 3	S01
Number of Units in Package 3	250
Package 3 Weight	1.042 kg
Package 3 Height	15 cm
Package 3 width	15 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>