



Main

| | |
|-------------------------------|------------------------------------------|
| Range of product | Telemecanique Limit switches XC Standard |
| Product or component type | Pre-cabled connection |
| Component name | ZCMC |
| Associated body | ZCMD25 |
| Number of poles | 2 |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Slow-break, break before make |

Complementary

| | |
|--------------------------|--------|
| Product compatibility | XCMD25 |
| Electrical connection | Cable |
| Cable length | 10 m |
| Wire insulation material | PvR |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.844 kg |
| Package 1 Height | 0.400 dm |
| Package 1 width | 1.900 dm |
| Package 1 Length | 1.900 dm |

Offer Sustainability

| | |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|