



Main

| | |
|-------------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Product or component type | Pre-cabled connection |
| Component name | ZCMC |
| Associated body | ZCMD39 |
| Number of poles | 3 |
| Contacts type and composition | 2 NC + 1 NO |
| Contact operation | Snap action |

Complementary

| | |
|--------------------------|--------|
| Product compatibility | XCMD39 |
| Electrical connection | Cable |
| Cable length | 5 m |
| Wire insulation material | PvR |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.453 kg |
| Package 1 Height | 0.300 dm |
| Package 1 width | 1.900 dm |
| Package 1 Length | 1.800 dm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|