

# ZCKE055

limit switch head ZCKE - without lever left and  
right actuation - +120 °C



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Rotary head
Product compatibility	XCKJ
Associated lever	ZCKY52 ZCKY11 ZCKY43 ZCKY59 ZCKY81 ZCKY41 ZCKY14 ZCKY91 ZCKY53 ZCKY13 ZCKY51
Associated body	ZCKJ7H29 ZCKJ6H29 ZCKJ404H7 ZCKJ9H7 ZCKJ11H7 ZCKJ41 ZCKJ6H7 ZCKJ11 ZCKJ7H7 ZCKJ9H29 ZCKJ2H7 ZCKJ4104H7 ZCKJD39 ZCKJD35H7 ZCKJD31H7 ZCKJ7 ZCKJ1H7 ZCKJ21 ZCKJ8 ZCKJ21H7 ZCKJ8H29 ZCKJ4H29 ZCKJD35H29 ZCKJ5H7 ZCKJD39H7 ZCKJ8H7 ZCKJ5H29 ZCKJ4H7 ZCKJD35 ZCKJ1H29 ZCKJ21H29 ZCKJ9 ZCKJD37 ZCKJ6 ZCKJ41H7 ZCKJD37H29 ZCKJ2 ZCKJ4104H29 ZCKJD37H7 ZCKJD31 ZCKJ2H29 ZCKJ5 ZCKJ4 ZCKJ1 ZCKJ41H29 ZCKJ4104 ZCKJD31H29 ZCKJ11H29 ZCKJ404H29 ZCKJD39H29 ZCKJ404
Movement of operating head	Rotary

Type of operator	Without operating lever spring return
Type of approach	Lateral approach, 1 or 2 programmable direction

### Complementary

Switch actuation	From left and/or right CW and/or CCW
Positive opening	With
Net weight	0.165 kg
Head material	Metal

### Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

### Packing Units

Package 1 Weight	0.168 kg
Package 1 Height	0.400 dm
Package 1 width	0.870 dm
Package 1 Length	0.480 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------