

# ZCKE625

Limit switch head, Limit switches XC Standard, ZCKE, steel roller plunger, +120 °C



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ7H29 ZCKJ7 ZCKJ4H29 ZCKJ4H7 ZCKJ11 ZCKJD31H29 ZCKJD37 ZCKJD37H29 ZCKJ8 ZCKJ9H7 ZCKJD35H7 ZCKJD35H29 ZCKJ21 ZCKJD31H7 ZCKJ8H29 ZCKJD39H7 ZCKJD35 ZCKJ1 ZCKJ2H7 ZCKJ21H7 ZCKJ21H29 ZCKJ4 ZCKJD31 ZCKJ41H7 ZCKJ11H7 ZCKJ9H29 ZCKJ5H29 ZCKJ5 ZCKJ2 ZCKJ11H29 ZCKJD39 ZCKJ1H29 ZCKJ41 ZCKJ6H29 ZCKJ41H29 ZCKJ2H29 ZCKJ8H7 ZCKJ6 ZCKJ7H7 ZCKJ9 ZCKJD39H29 ZCKJ1H7 ZCKJ6H7 ZCKJ5H7 ZCKJD37H7
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal
Type of approach	Lateral approach, 2 directions

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.155 kg
Head material	Metal

## Environment

Ambient air temperature for operation	10...120 °C
Ambient air temperature for storage	10...120 °C
Environmental characteristic	High temperature

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	153 g
Package 1 Height	4 cm
Package 1 width	4.5 cm
Package 1 Length	8.7 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------