

ZCKE65

limit switch head ZCKE - metal side plunger
with vertical roller



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ2H29 ZCKJD31 ZCKJ8H29 ZCKJ21H29 ZCKJD37H7 ZCKJ7 ZCKJD37H29 ZCKJ9H29 ZCKJ2 ZCKJ7H7 ZCKJ21 ZCKJD35H7 ZCKJD31H7 ZCKJ8 ZCKJ5 ZCKJD39 ZCKJ11H7 ZCKJ1 ZCKJ11H29 ZCKJ2H7 ZCKJ11 ZCKJ9 ZCKJ6 ZCKJ1H29 ZCKJ8H7 ZCKJ21H7 ZCKJ5H29 ZCKJ9H7 ZCKJ6H7 ZCKJD35 ZCKJ7H29 ZCKJD37 ZCKJD35H29 ZCKJD39H7 ZCKJ1H7 ZCKJD31H29 ZCKJD39H29 ZCKJ5H7 ZCKJ6H29
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with vertical roller)
Type of approach	Vertical approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.187 kg
Package 1 Height	0.400 dm
Package 1 width	0.460 dm
Package 1 Length	0.860 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------