



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKT XCKD XCKP

Associated body	ZCD37 ZCMD37L1 ZCP27 ZCT27G11 ZCMD21C12 ZCD35 ZCMD37L2 ZCMD21L2 ZCD31 ZCMD25L5 ZCT26N12 ZCMD81L2 ZCT28G11 ZCD28 ZCD27 ZCT21N12 ZCMD41L2 ZCD26 ZCMD37L5 ZCMD21M12 ZCT26P16 ZCP29M12 ZCMD41L1 ZCD29M12 ZCD21 ZCMD29L1 ZCMD29L5 ZCT21G11 ZCP21M12 ZCMD61C12 ZCMD81L5 ZCMD39L5 ZCT27N12 ZCT25G11 ZCMD29C12 ZCMD21L08U78 ZCMD25L2 ZCD39 ZCP26 ZCP29 ZCMD69C12 ZCP39 ZCP25 ZCT25N12 ZCMD25L1 ZCT28N12 ZCT27P16 ZCP35 ZCD25 ZCMD39L1 ZCD29 ZCT26G11 ZCD21M12 ZCMD21L1 ZCT21P16 ZCMD41L5 ZCP37 ZCP28 ZCMD21L08R12 ZCP21 ZCMD29L2 ZCT25P16 ZCMD81L1 ZCMD39L2 ZCMD61M12 ZCP31 ZCMD21L5 ZCT28P16
Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach, 1 direction

Complementary

Positive opening With

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.009 kg
Package 1 Height	0.150 dm
Package 1 width	0.300 dm
Package 1 Length	0.250 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------