

ZCE1A

Limit switch head, Limit switches XC Standard,
ZCE, metal end plunger with silicone boot





Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKT XCKD XCKP

Associated body	ZCT28N12 ZCMD21M12 ZCT21N12 ZCD25 ZCP29 ZCP31 ZCP26 ZCD26 ZCP21 ZCMD81L2 ZCMD81L1 ZCT25P16 ZCMD29L5 ZCP39 ZCMD39L2 ZCT26N12 ZCT25G11 ZCMD29C12 ZCMD29L2 ZCMD25L2 ZCT27N12 ZCMD41L1 ZCMD37L1 ZCD31 ZCMD81L5 ZCMD61C12 ZCMD41L2 ZCT28G11 ZCT26G11 ZCMD61M12 ZCMD21L08R12 ZCMD25L5 ZCMD25L1 ZCD21 ZCMD37L2 ZCT27G11 ZCMD29L1 ZCD37 ZCT28P16 ZCMD21L5 ZCT21P16 ZCP29M12 ZCD29M12 ZCP35 ZCD39 ZCMD69C12 ZCMD41L5 ZCMD39L5 ZCT21G11 ZCMD37L5 ZCD35 ZCP28 ZCMD21C12 ZCMD21L2 ZCMD39L1 ZCP27 ZCT26P16 ZCP37 ZCMD21L1 ZCT25N12 ZCD29 ZCP21M12 ZCP25 ZCD21M12 ZCT27P16 ZCD27 ZCD28 ZCMD21L08U78
Movement of operating head	Linear
Type of operator	End plunger spring return metal (with silicone boot)
Type of approach	Vertical approach, 1 direction

Complementary

Positive opening	With
------------------	------

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.014 kg
Package 1 Height	0.200 dm
Package 1 width	0.300 dm
Package 1 Length	0.450 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------