



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKT XCMD XCKP XCKD

Associated body	ZCP29 ZCD39 ZCP26 ZCMD69C12 ZCD21M12 ZCMD29L2 ZCMD39L5 ZCD27 ZCMD29C12 ZCT25G11 ZCT28N12 ZCMD21M12 ZCP21M12 ZCD28 ZCMD61C12 ZCT27N12 ZCMD21C12 ZCMD81L5 ZCT27G11 ZCT26P16 ZCMD21L2 ZCT25N12 ZCP25 ZCP29M12 ZCT27P16 ZCT21P16 ZCD35 ZCMD41L2 ZCD29M12 ZCMD25L5 ZCMD21L08U78 ZCT21G11 ZCT28G11 ZCP31 ZCMD37L5 ZCD29 ZCT26N12 ZCMD39L2 ZCP21 ZCT25P16 ZCP37 ZCMD61M12 ZCD37 ZCP39 ZCMD25L2 ZCMD37L2 ZCP35 ZCT26G11 ZCD26 ZCMD41L1 ZCD25 ZCMD29L1 ZCMD39L1 ZCP27 ZCMD41L5 ZCMD81L2 ZCD31 ZCMD37L1 ZCMD21L1 ZCMD29L5 ZCMD25L1 ZCMD21L5 ZCT28P16 ZCD21 ZCP28 ZCMD81L1 ZCT21N12 ZCMD21L08R12
Movement of operating head	Linear
Type of operator	Roller lever plunger spring return metal (retractable)
Type of approach	Lateral approach, 1 direction

## Complementary

Switch actuation	By 30° cam
Positive opening	With

## Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

## Packing Units

Package 1 Weight	0.030 kg
Package 1 Height	0.200 dm
Package 1 width	0.500 dm
Package 1 Length	0.350 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------