



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKT XCKP XCKD

Associated body	ZCMD21C12 ZCMD21L08U78 ZCMD25L5 ZCT21G11 ZCMD41L1 ZCT27P16 ZCD29M12 ZCD21 ZCP37 ZCMD41L2 ZCD25 ZCMD21L5 ZCMD39L1 ZCP27 ZCP35 ZCP28 ZCT28G11 ZCT26N12 ZCD39 ZCT25G11 ZCMD39L5 ZCT21P16 ZCP25 ZCMD81L1 ZCD31 ZCT28P16 ZCMD81L5 ZCMD69C12 ZCT27N12 ZCD21M12 ZCT25N12 ZCD26 ZCP21M12 ZCP39 ZCMD25L1 ZCT25P16 ZCT21N12 ZCP29 ZCMD37L2 ZCMD61C12 ZCD28 ZCD37 ZCT26G11 ZCP21 ZCMD81L2 ZCMD37L1 ZCMD25L2 ZCP29M12 ZCMD29L1 ZCMD37L5 ZCMD41L5 ZCMD21M12 ZCT28N12 ZCT26P16 ZCMD21L08R12 ZCMD21L1 ZCP26 ZCD27 ZCMD29L2 ZCT27G11 ZCMD39L2 ZCMD61M12 ZCP31 ZCD35 ZCMD21L2 ZCMD29C12 ZCMD29L5 ZCD29
Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral or vertical approach, 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.026 kg
Package 1 Height	0.160 dm
Package 1 width	0.500 dm
Package 1 Length	0.300 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------