





Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCMD XCKD XCKT XCKP

Associated body	ZCP39 ZCMD29C12 ZCMD37L1 ZCMD41L2 ZCMD25L5 ZCT26N12 ZCT21P16 ZCD29 ZCT21N12 ZCT28G11 ZCMD21L2 ZCMD39L5 ZCT26P16 ZCMD39L2 ZCMD37L2 ZCP27 ZCP21M12 ZCD31 ZCMD61C12 ZCD26 ZCD21M12 ZCT26G11 ZCMD29L2 ZCMD25L2 ZCMD21C12 ZCMD21M12 ZCP35 ZCMD21L1 ZCT28N12 ZCD35 ZCMD29L1 ZCD25 ZCMD81L2 ZCT27P16 ZCMD69C12 ZCD29M12 ZCMD25L1 ZCT27G11 ZCD37 ZCD21 ZCMD21L08U78 ZCT27N12 ZCP26 ZCMD81L5 ZCP29 ZCP29M12 ZCMD41L1 ZCT21G11 ZCP25 ZCMD41L5 ZCT25N12 ZCMD29L5 ZCMD39L1 ZCD28 ZCT25G11 ZCD27 ZCD39 ZCMD37L5 ZCT25P16 ZCP21 ZCP31 ZCMD81L1 ZCMD21L08R12 ZCMD61M12 ZCP28 ZCMD21L5 ZCP37 ZCT28P16
Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal (with horizontal roller)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	Without

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.057 kg
Package 1 Height	0.180 dm
Package 1 width	0.500 dm
Package 1 Length	0.320 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------