



Main

| | |
|----------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ |
| Associated head | ZCKE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal (-) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -25...70 °C for standard environment -40...70 °C for low temperature 10...120 °C for high temperature |
| Ambient air temperature for storage | -40...70 °C standard environment -40...70 °C low temperature 10...120 °C high temperature |
| Environmental characteristic | High temperature Corrosive Low temperature |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 31 g |
| Package 1 Height | 2 cm |
| Package 1 width | 2 cm |
| Package 1 Length | 5.5 cm |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 100 |
| Package 2 Weight | 3.343 kg |
| Package 2 Height | 15 cm |
| Package 2 width | 15 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|