



## Main

|                            |  |
|----------------------------|--|
| Range of product           | Telemecanique Limit switches XC Standard                           |
| Series name                | Standard format  |
| Product or component type  | Limit switch lever   |
| Device short name          | ZCKY   |
| Product compatibility      | XCKL<br>XCKJ<br>XCKM<br>XCKS                                       |
| Associated head            | ZCKD05<br>ZCKE05   |
| Movement of operating head | Rotary   |
| Type of operator           | Rod lever spring return thermoplastic (round rod 6 mm, L = 200 mm) |
| Type of approach           | Lateral approach   |

## Complementary

|                  |                    |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without            |

## Environment

|                                       |   |
|---------------------------------------|---|
| Ambient air temperature for operation | -25...70 °C for standard environment<br>-40...70 °C for low temperature |
| Ambient air temperature for storage   | -40...70 °C standard environment<br>-40...70 °C low temperature         |
| Environmental characteristic          | Standard environment<br>Low temperature                                 |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.025 kg |
| Package 1 Height | 0.100 dm |
| Package 1 width  | 0.250 dm |
| Package 1 Length | 2.020 dm |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|