

XUYFVERSD61

Photoelectric sensors XU, glass fibre optic for sensor, thru beam, straight, standard, 0.6 m, Sn200mm



Main

Range of product	Telemecanique Photoelectric sensors XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	Standard
[Sn] nominal sensing distance	200 mm XUYAFV
End fitting type	Straight with nickel plated brass, M4 x 0.7

Complementary

Electronic sensor type	Photo-electric sensor
Optic fiber material	50 µ glass
Sheath material	PVC + thermo polyolefine
Detection system	Thru beam
Optic fiber length	0.6 m
Minimum bending radius	10 mm
Head mounting	M4 x 0.7
Net weight	0.042 kg

Environment

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	42.9 g
Package 1 Height	1.5 cm
Package 1 width	13.6 cm
Package 1 Length	13.6 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------