

XUYFVERTD201

Photoelectric sensors XU, glass fibre optic for sensor, thru beam, straight, High temp, 2 m, Sn200mm



Main

Range of product	Telemecanique Photoelectric sensors XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	High temperature
[Sn] nominal sensing distance	200 mm XUYAFV
End fitting type	Straight with nickel plated brass, M4 x 0.7

Complementary

Electronic sensor type	Photo-electric sensor
Optic fiber material	50 μ glass
Sheath material	Flexible stainless steel
Detection system	Thru beam
Optic fiber length	2 m
Minimum bending radius	30 mm
Head mounting	M4 x 0.7
Net weight	0.06 kg

Environment

Ambient air temperature for operation	-25...200 °C
---------------------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	170 g
Package 1 Height	2.5 cm
Package 1 width	13.3 cm
Package 1 Length	18.3 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------