



## Main

|                               |                                        |
|-------------------------------|----------------------------------------|
| Range of product              | Telemecanique Photoelectric sensors XU |
| Series name                   | General purpose single mode            |
| Electronic sensor type        | Photo-electric sensor                  |
| Sensor name                   | XU5                                    |
| Sensor design                 | Cylindrical M18                        |
| Detection system              | Diffuse                                |
| Material                      | Metal                                  |
| Line of sight type            | Axial                                  |
| Type of output signal         | Discrete                               |
| Supply circuit type           | AC/DC                                  |
| Wiring technique              | 2-wire                                 |
| Discrete output function      | 1 NO                                   |
| Electrical connection         | Cable                                  |
| Cable length                  | 2 m                                    |
| Product specific application  | -                                      |
| Emission                      | Infrared diffuse                       |
| [Sn] nominal sensing distance | 0.4 m diffuse                          |

## Complementary

|                           |                                                                             |
|---------------------------|-----------------------------------------------------------------------------|
| Enclosure material        | Nickel plated brass                                                         |
| Lens material             | PMMA                                                                        |
| Maximum sensing distance  | 0.6 m                                                                       |
| Output type               | Solid state                                                                 |
| Add on output             | Without                                                                     |
| Wire insulation material  | PvR                                                                         |
| Status LED                | 1 LED (yellow) for output state                                             |
| [Us] rated supply voltage | 24...240 V AC/DC                                                            |
| Supply voltage limits     | 20...264 V AC/DC                                                            |
| Maximum residual current  | 1.5 mA open state AC/DC                                                     |
| Switching capacity in mA  | 10...200 mA (to be used with 0.4 A quick-blow fuse in series with the load) |
| Switching frequency       | <= 25 Hz                                                                    |
| Maximum voltage drop      | <6 V (closed state)                                                         |
| Maximum delay first up    | 300 ms                                                                      |
| Maximum delay response    | 20 ms                                                                       |
| Maximum delay recovery    | 20 ms                                                                       |
| Setting-up                | Sensitivity adjustment                                                      |
| Diameter                  | 18 mm                                                                       |
| Length                    | 82 mm                                                                       |
| Net weight                | 0.15 kg                                                                     |

## Environment

|                                       |                                                                           |
|---------------------------------------|---------------------------------------------------------------------------|
| Product certifications                | CE<br>CSA<br>UL                                                           |
| Ambient air temperature for operation | -25...55 °C                                                               |
| Ambient air temperature for storage   | -40...70 °C                                                               |
| Vibration resistance                  | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27                     |
| IP degree of protection               | IP67 double insulation conforming to IEC 60529                            |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 136 g    |
| Package 1 Height             | 4.1 cm   |
| Package 1 width              | 9.4 cm   |
| Package 1 Length             | 13 cm    |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 22       |
| Package 2 Weight             | 3.326 kg |
| Package 2 Height             | 15 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---




---

## Wiring Schemes

---

### 2-wire AC or DC




BU : Blue  
BN : Brown

---

Detection Curves

---

Diffuse System



1 : White 90%

2 : Grey 18%

Object 10 x 10 cm