

XUYP952R

Photoelectric sensors XU, photo electric sensor, XUY, diffuse, Sn 4 m, 24...240VAC/DC, terminals



Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application, conveyor system and access control
Electronic sensor type	Photo-electric sensor
Sensor name	XUY
Sensor design	Compact
Detection system	Diffuse
Material	Plastic
Type of output signal	Discrete
Discrete output type	Relay
Discrete output function	1 NO or 1 NC programmable
Electrical connection	Screw terminal
Product specific application	Materials handling Access control Detection of belt breakage
Emission	Infrared
[Sn] nominal sensing distance	4 m

Complementary

Enclosure material	Polycarbonate
Output type	Relay
Status LED	1 LED color: green for output status 1 LED color: red for alignment assistance 1 LED color: red for dirty optics 1 LED color: red for limit of detection 1 LED color: red for time delay 1 LED color: red for time function indicator
Supply voltage limits	10...30 V DC
Switching capacity in mA	3 A
Switching frequency	> 25 Hz
Maximum voltage drop	<2 V at 100 mA (closed state) <1 V at 10 mA (closed state)
Power consumption in VA	2 VA no load
Time delay range	0...10 s retriggerable delay for output circuit
Setting-up	Teach mode and/or fine manual adjustment
Net weight	0.15 kg

Environment

Product certifications	CE
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-20...80 °C
Immunity to ambient light	10000 Lux incandescent bulb at 5° of optical axis 20000 lux natural light at 5° to the optical axis
IP degree of protection	IP65 conforming to IEC 60529 IP67 conforming to IEC 60529

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	143 g
Package 1 Height	3.5 cm
Package 1 width	7.5 cm
Package 1 Length	13.3 cm
Unit Type of Package 2	S01
Number of Units in Package 2	10
Package 2 Weight	1.621 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------