

# XS518BLPAM12

Inductive proximity sensors XS, inductive sensor XS5 M18, L74mm, brass, Sn5mm, 12...48 VDC, M12



## Main

|                                    |                                                               |
|------------------------------------|---------------------------------------------------------------|
| Range of product                   | Telemecanique Inductive proximity sensors XS                  |
| Series name                        | General purpose                                               |
| Sensor type                        | Inductive proximity sensor                                    |
| Device application                 | -                                                             |
| Sensor name                        | XS5                                                           |
| Sensor design                      | Cylindrical M18                                               |
| Size                               | 74 mm                                                         |
| Body type                          | Fixed                                                         |
| Detector flush mounting acceptance | Flush mountable                                               |
| Material                           | Metal                                                         |
| Type of output signal              | Discrete                                                      |
| Wiring technique                   | 3-wire                                                        |
| [Sn] nominal sensing distance      | 5 mm                                                          |
| Discrete output function           | 1 NO                                                          |
| Output circuit type                | DC                                                            |
| Discrete output type               | PNP                                                           |
| Electrical connection              | 4 pins M12 male connector                                     |
| [Us] rated supply voltage          | 12...48 V DC with reverse polarity protection                 |
| Switching capacity in mA           | <= 200 mA DC with overload and short-circuit protection       |
| IP degree of protection            | IP67 conforming to IEC 60529<br>IP69K conforming to DIN 40050 |

## Complementary

|                        |                              |
|------------------------|------------------------------|
| Thread type            | M18 x 1                      |
| Detection face         | Frontal                      |
| Front material         | PPS                          |
| Enclosure material     | Nickel plated brass          |
| Operating zone         | 0...4 mm                     |
| Differential travel    | 1...15% of Sr                |
| Status LED             | Output state: 1 LED (yellow) |
| Supply voltage limits  | 10...58 V DC                 |
| Switching frequency    | <= 2000 Hz                   |
| Maximum voltage drop   | <2 V (closed)                |
| Current consumption    | <= 10 mA no-load             |
| Maximum delay first up | 10 ms                        |
| Maximum delay response | 0.15 ms                      |
| Maximum delay recovery | 0.35 ms                      |
| Marking                | CE                           |
| Threaded length        | 52 mm                        |
| Height                 | 18 mm                        |
| Length                 | 74 mm                        |

## Environment

|                                       |                                                                         |
|---------------------------------------|-------------------------------------------------------------------------|
| Product certifications                | UL<br>CSA                                                               |
| Ambient air temperature for operation | -25...70 °C                                                             |
| Ambient air temperature for storage   | -40...85 °C                                                             |
| Vibration resistance                  | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                            |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 74 g     |
| Package 1 Height             | 4.1 cm   |
| Package 1 width              | 6.4 cm   |
| Package 1 Length             | 9.4 cm   |
| Unit Type of Package 2       | BAG      |
| Number of Units in Package 2 | 1        |
| Package 2 Weight             | 74 g     |
| Package 2 Height             | 2 cm     |
| Package 2 width              | 20 cm    |
| Package 2 Length             | 15 cm    |
| Unit Type of Package 3       | S02      |
| Number of Units in Package 3 | 44       |
| Package 3 Weight             | 3.093 kg |
| Package 3 Height             | 15 cm    |
| Package 3 width              | 30 cm    |
| Package 3 Length             | 40 cm    |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|