

# XSAV11801L10

inductive sensor XSAV - M30 - Sn10mm -  
6..150c/mn - 24..240VAC/DC - cable 10m



## Main

|                                    |                                              |
|------------------------------------|----------------------------------------------|
| Range of product                   | Telemecanique Inductive proximity sensors XS |
| Series name                        | Application                                  |
| Product or component type          | Sensor                                       |
| Sensor type                        | Inductive proximity sensor                   |
| Device application                 | Rotation monitoring                          |
| Sensor name                        | XSA                                          |
| Sensor design                      | Cylindrical M30                              |
| Size                               | 81 mm                                        |
| Body type                          | Fixed                                        |
| Detector flush mounting acceptance | Flush mountable                              |
| Material                           | Metal                                        |
| Enclosure material                 | Nickel plated brass                          |
| Type of output signal              | Discrete                                     |
| Wiring technique                   | 2-wire                                       |
| [Sn] nominal sensing distance      | 10 mm                                        |
| Discrete output function           | 1 NC                                         |
| Output circuit type                | AC/DC                                        |
| Electrical connection              | Cable                                        |
| Cable length                       | 10 m                                         |
| [Us] rated supply voltage          | 24...210 V DC<br>24...240 V AC 50/60 Hz      |
| Switching capacity in mA           | 5...200 mA DC<br>5...350 mA AC               |
| IP degree of protection            | IP67 conforming to IEC 60529                 |

## Complementary

|                            |                           |
|----------------------------|---------------------------|
| Thread type                | M30 x 1.5                 |
| Detection face             | Frontal                   |
| Front material             | PPS                       |
| Sensing range              | > 8...15 mm               |
| Adjustable frequency range | 6...150 cyc/mn            |
| Operating zone             | 0...8 mm                  |
| Differential travel        | 3...15% of Fr             |
| Repeat accuracy            | 3% of Sr                  |
| Cable composition          | 2 x 0.34 mm <sup>2</sup>  |
| Wire insulation material   | PvR                       |
| Status LED                 | Output state: 1 LED (red) |
| Supply voltage limits      | 20...264 V AC/DC          |
| Maximum residual current   | 1.5 mA open state         |
| Switching frequency        | <= 100 Hz                 |
| Maximum voltage drop       | <5.7 V (closed)           |
| Run-up delay at power-up   | 9 s standard              |
| Marking                    | CE                        |
| Threaded length            | 67 mm                     |

|            |        |
|------------|--------|
| Length     | 81 mm  |
| Net weight | 0.3 kg |

## Environment

|                                       |                  |
|---------------------------------------|------------------|
| Product certifications                | CSA<br>UL<br>CCC |
| Ambient air temperature for operation | -25...70 °C      |
| Ambient air temperature for storage   | -40...85 °C      |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 242 g   |
| Package 1 Height             | 4.5 cm  |
| Package 1 width              | 14.8 cm |
| Package 1 Length             | 8 cm    |


## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions




(1) LED

---

Minimum Mounting Distances

---


Side by side



e (1) 20 mm/0.79 in

≥


Face to face



e (2) 120 mm/4.72 in

≥

Facing a metal object



e (3) 30 mm/1.18 in.


≥

---

## Wiring Schemes

---

2-wire AC or DC




BU : Blue  
BN : Brown

---

Performance Curves

---

Standard Steel Target : 30x30x1 mm



- (1) Pick-up points  
(2) Drop-out points (object approaching from the side)  
(y) Sensing distance in mm