



### Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	1 plate for push-button controls 1 terminal block 8 holes 2 wiring straps 1 terminal block support 4 plates for 65 x 85 power outlets
Mounting plate description	Without mounting plate

### Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	8
Total number of 18 mm modules	8
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Number of openings of interface	4
Number of plates	1 for push-button controls 4 for 65 x 85 power outlets
Provided equipment	2 wiring strap 1 plate for push-button control 4 plate for 65 x 85 power outlet 1 terminal block 8 holes 1 terminal block support
Type of front cover	Transparent
Power dissipation in W	15 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Number of terminal blocks	1 with 8 outgoers
Distribution block outgoers	4 x 10 mm <sup>2</sup> 4 x 16 mm <sup>2</sup>
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	236 mm
Height	460 mm
Depth	160 mm
Internal depth	91 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)
Targeted country	France

## Environment

Standards	EN 50102 IEC 670 IEC 60529 IEC 60439-3 EN 50262
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.05 kg
Package 1 Height	17.1 cm
Package 1 width	26.1 cm
Package 1 Length	47.1 cm
Unit Type of Package 2	P12
Number of Units in Package 2	42
Package 2 Weight	101.922 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------