



### Main

|                                     |   |
|-------------------------------------|---|
| Range                               | Kaedra  |
| Product or component type           | Weatherproof enclosure  |
| Enclosure type                      | Enclosure for plug and socket   |
| Accessories included with enclosure | 1 terminal block support<br>1 terminal block 8 holes<br>3 plates for 65 x 85 power outlets<br>1 plate for push-button controls<br>2 wiring straps |
| Mounting plate description          | Without mounting plate  |

### Complementary

|                                 |   |
|---------------------------------|---|
| Enclosure mounting              | Surface   |
| Number of 18 mm modules per row | 12  |
| Total number of 18 mm modules   | 12  |
| Number of horizontal rows       | 1   |
| Electrical insulation class     | Class II<br>Double insulation   |
| Number of openings of interface | 3   |
| Number of plates                | 1 for push-button controls<br>3 for 65 x 85 power outlets   |
| Provided equipment              | 2 wiring strap<br>1 plate for push-button control<br>3 plate for 65 x 85 power outlet<br>1 terminal block 8 holes<br>1 terminal block support |
| Type of front cover             | Transparent   |
| Power dissipation in W          | 23 W  |
| [In] rated current              | 63 A  |
| Type of rail                    | DIN   |
| Number of pre-cutouts PG ISO    | 17  |
| Number of terminal blocks       | 1 with 8 outgoers   |
| Distribution block outgoers     | 4 x 10 mm <sup>2</sup><br>4 x 16 mm <sup>2</sup>  |
| Locking options description     | Optional keylock  |
| Enclosure material              | Self-extinguishing polymer  |
| Base dimension                  | 90 x 100 mm   |
| Width                           | 340 mm  |
| Height                          | 335 mm  |
| Depth                           | 160 mm  |
| Internal depth                  | 91 mm   |
| Colour                          | Door: transparent green<br>Enclosure: light grey (RAL 7035)   |
| Targeted country                | France  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 670<br>IEC 60439-3<br>EN 50262<br>IEC 60529<br>EN 50102   |
| Fire resistance                       | 750 °C conforming to IEC 60695-2-1  |
| IP degree of protection               | IP65 conforming to IEC 60529  |
| IK degree of protection               | IK09 conforming to EN 50102   |
| Environmental characteristics (UV)    | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage category                  | II  |
| Ambient air temperature for operation | -25...60 °C   |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 2.19 kg  |
| Package 1 Height             | 17.2 cm  |
| Package 1 width              | 35 cm    |
| Package 1 Length             | 36 cm    |
| Unit Type of Package 2       | P12      |
| Number of Units in Package 2 | 36       |
| Package 2 Weight             | 90.84 kg |
| Package 2 Height             | 80 cm    |
| Package 2 width              | 80 cm    |
| Package 2 Length             | 120 cm   |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|