



Main

| | |
|-------------------------------------|---|
| Range | Kaedra |
| Product or component type | Weatherproof enclosure |
| Enclosure type | Enclosure for plug and socket |
| Accessories included with enclosure | 1 terminal block 8 holes 1 plate for 65 x 65 or 75 x 75 power outlets 1 terminal block support 2 wiring straps |
| Mounting plate description | Without mounting plate |

Complementary

| | |
|---------------------------------|---|
| Enclosure mounting | Surface |
| Number of 18 mm modules per row | 12 |
| Total number of 18 mm modules | 12 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Class II Double insulation |
| Number of openings of interface | 3 |
| Number of plates | 1 for 65 x 65 or 75 x 75 power outlets |
| Provided equipment | 2 wiring strap 1 plate for 65 x 65 or 75 x 75 power outlet 1 terminal block 8 holes 1 terminal block support |
| Type of front cover | Transparent |
| Power dissipation in W | 23 W |
| [In] rated current | 63 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 17 |
| Number of terminal blocks | 1 with 8 outgoers |
| Distribution block outgoers | 4 x 10 mm ² 4 x 16 mm ² |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Base dimension | 103 x 225 mm |
| Width | 340 mm |
| Height | 460 mm |
| Depth | 160 mm |
| Internal depth | 91 mm |
| Colour | Door: transparent green Enclosure: light grey (RAL 7035) |
| Targeted country | France |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60529 IEC 60439-3 EN 50262 IEC 670 EN 50102 |
| Fire resistance | 750 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| Environmental characteristics (UV) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 2.607 kg |
| Package 1 Height | 16.8 cm |
| Package 1 width | 36 cm |
| Package 1 Length | 47 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 28 |
| Package 2 Weight | 84.996 kg |
| Package 2 Height | 80 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|