



### Main

|                            |                                      |
|----------------------------|--------------------------------------|
| Range                      | Kaedra                               |
| Product or component type  | Weatherproof enclosure               |
| Enclosure type             | Versatile enclosure for power outlet |
| Mounting plate description | Without mounting plate               |

### Complementary

|                                 |                                                             |
|---------------------------------|-------------------------------------------------------------|
| Enclosure mounting              | Surface                                                     |
| Number of 18 mm modules per row | 12                                                          |
| Total number of 18 mm modules   | 12                                                          |
| Number of horizontal rows       | 1                                                           |
| Electrical insulation class     | Double insulation<br>Class II                               |
| Type of front cover             | Transparent                                                 |
| Power dissipation in W          | 23 W                                                        |
| [In] rated current              | 63 A                                                        |
| Type of rail                    | DIN                                                         |
| Number of pre-cutouts PG ISO    | 17                                                          |
| Locking options description     | Optional keylock                                            |
| Enclosure material              | Self-extinguishing polymer                                  |
| Width                           | 340 mm                                                      |
| Height                          | 460 mm                                                      |
| Depth                           | 160 mm                                                      |
| Internal depth                  | 91 mm                                                       |
| Colour                          | Door: transparent green<br>Enclosure: light grey (RAL 7035) |
| Targeted country                | France                                                      |

### Environment

|                                       |                                                                                                                 |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Standards                             | EN 50262<br>IEC 60529<br>IEC 670<br>EN 50102<br>IEC 60439-3                                                     |
| Fire resistance                       | 750 °C conforming to IEC 60695-2-1                                                                              |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                    |
| IK degree of protection               | IK09 conforming to EN 50102                                                                                     |
| Environmental characteristics (UV)    | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage category                  | II                                                                                                              |
| Ambient air temperature for operation | -25...60 °C                                                                                                     |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 2.687 kg  |
| Package 1 Height             | 16.8 cm   |
| Package 1 width              | 36 cm     |
| Package 1 Length             | 47 cm     |
| Unit Type of Package 2       | P12       |
| Number of Units in Package 2 | 28        |
| Package 2 Weight             | 87.236 kg |
| Package 2 Height             | 80 cm     |
| Package 2 width              | 80 cm     |
| Package 2 Length             | 120 cm    |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|