## Product data sheet Characteristics

## **DE1DS1A04**

# TeSys LE - enclosure for DOL starter - without pushbuttons





### Main

Range of product	TeSys
Range	TeSys
Device short name	DE1D
Product or component type	Enclosure
Material	Polycarbonate
Device composition	Contactor ordered separately Thermal overload relay ordered separately
Product compatibility	LE1D12 LE1D09
Control type	Without

Complementary		
Cable entry number	2 ISO20 top	
	2 ISO20 bottom	
	2 Pg 13 bottom	
	2 Pg 16 bottom	
Height	166 mm	
Width	88 mm	
Depth	135 mm	
Net weight	0.3 kg	

### Environment

IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK07 conforming to IEC 60529	
Ambient air temperature for operation	-540 °C	
Environmental characteristic	Standard environment	

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	491 g
Package 1 Height	20 cm
Package 1 width	21.5 cm
Package 1 Length	23 cm
Unit Type of Package 2	P06
Number of Units in Package 2	30
Package 2 Weight	27.73 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	60 cm

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

### Contractual warranty

Warranty 18 months	
--------------------	--