



Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Interface enclosure
Accessories included with enclosure	4 plates for push-button controls 1 plate for 65 x 85 power outlets
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
Electrical insulation class	Class II Double insulation
Number of openings of interface	4
Number of plates	1 for 65 x 85 power outlets 4 for push-button controls
Provided equipment	1 plate for 65 x 85 power outlet 4 plate for push-button control
Type of front cover	Opaque
[In] rated current	63 A
Number of pre-cutouts PG ISO	3
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	138 mm
Height	610 mm
Depth	160 mm
Internal depth	88 mm
Colour	Enclosure: light grey (RAL 7035)
Targeted country	France

Environment

Standards	EN 50262 IEC 670 IEC 60529 EN 50102 IEC 60439-3
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.595 kg
Package 1 Height	13.5 cm
Package 1 width	16 cm
Package 1 Length	62 cm
Unit Type of Package 2	P12
Number of Units in Package 2	64
Package 2 Weight	114.08 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------