



Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Interface
Width	200 mm
Height	600 mm
Depth	136 mm
Nb of 18 mm modules per row	24
Nb of horizontal rows	3
Electrical insulation class	Double insulation Class II
Provided equipment	1 x identification label 1 x plain plate per row 1 x front face and back connection
Type of door	Without

Complementary

Enclosure mounting	Surface
9 mm pitches	48
Total number of 18 mm modules	21
Number of plates	3 for plain plate
[In] rated current	160 A
[Ui] rated insulation voltage	400 V
Type of rail	Without
Mounting plate description	Without mounting plate
Cable entry	Cut-out plates Removable plates Trunking Cable or tube
Enclosure material	Back part: technoplastic Front face: technoplastic Back part: metal
Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
Market segment	Small commercial Residential
Embedding depth	0 mm
Internal depth	120 mm

Environment

Fire resistance	Back part: 750 °C Front face: 750 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.26 kg
Package 1 Height	14.5 cm
Package 1 width	22 cm
Package 1 Length	61 cm
Unit Type of Package 2	P12
Number of Units in Package 2	34
Package 2 Weight	122.84 kg
Package 2 Height	120 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------