



Main

Range	Linergy
Range of product	Linergy
Product or component type	Busbar support
Product name	Linergy BS
Range compatibility	Linergy BS busbar Prisma G enclosure

Complementary

Cubicle-device connection	Linergy BS lateral busbar
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Permissible current	160 A - busbar cross section: 15 x 5 mm 250 A - busbar cross section: 20 x 5 mm 400 A - busbar cross section: 32 x 5 mm 630 A - busbar cross section: 32 x 8 mm
[I _{cw}] rated short-time withstand current	10 KA (1 s) at 160 A for 450 mm between support centres 20 KA (1 s) at 400 A for 300 mm between support centres 13 KA (1 s) at 250 A for 450 mm between support centres 15 KA (1 s) at 400 A for 450 mm between support centres 15 KA (1 s) at 630 A for 450 mm between support centres 20 KA (1 s) at 630 A for 300 mm between support centres 25 KA (0.6 s) at 400 A for 300 mm between support centres 25 KA (1 s) at 630 A for 300 mm between support centres
Quantity per set	Set of 1
Net weight	0.2 kg

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	200 g
Package 1 Height	2 cm
Package 1 width	11.5 cm
Package 1 Length	23.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Weight	2.35 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12

Number of Units in Package 3	320
Package 3 Weight	81.28 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile