



Main

Range	Linerigy
Range of product	Linerigy
Product or component type	Connection
Product name	Linerigy FM
Product name	Prisma G enclosure Prisma P enclosure Prisma iPM L enclosure Prisma iPM M enclosure Linerigy FM device feeder
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linerigy FM distribution block Linerigy BS rear busbar
Poles description	4P
Installation description	Enclosure - width 600 mm
[Ie] rated operational current	200 A
[In] rated current	200 A
Colour	Anthracite grey (RAL 7016)
Net weight	0.08 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	80 g
Package 1 Height	1.5 cm
Package 1 width	6 cm
Package 1 Length	10.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	3.3 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Weight	12.8 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product