



### Main

Range	Linergy
Range of product	Linergy
Product or component type	Flexible connection
Product name	Linergy DX
Product name	Prisma G enclosure Prisma P enclosure Prisma Pack 160 enclosure Prisma Pack 250 enclosure Linergy DX distribution block
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### Complementary

Cubicle-device connection	Linergy DX distribution block
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 800 mm Pack enclosure - width 555 mm Pack enclosure - width 600 mm
Installed device	Multi 9: fixed NG125 without earth leakage protection - control: toggle Multi 9: fixed NG125 with earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle vertical installation ComPact: fixed INS63 - control: direct front rotary handle vertical installation ComPact: fixed INS100 - control: direct front rotary handle vertical installation ComPact: fixed INS125 - control: direct front rotary handle vertical installation ComPact: fixed INS160 - control: direct front rotary handle vertical installation Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle Multi 9: fixed NG125 NA - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle vertical installation
Condition of use	Additional connector needed for INS40...160 (to be ordered separately)
[I <sub>e</sub> ] rated operational current	125 A
[I <sub>n</sub> ] rated current	125 A
Length	240 mm
Net weight	0.52 kg





## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	520 g
Package 1 Height	2 cm
Package 1 width	10.5 cm
Package 1 Length	34 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	15
Package 2 Weight	8.12 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Weight	135.12 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product