



Main

Range	Linergy
Range of product	Linergy
Product or component type	One-piece connection
Product name	Linergy BW
Product name	Prisma P enclosure Prisma G enclosure Linergy BW busbar
Provided equipment	With connection
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy BW busbar
Poles description	4P
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 550 mm
Installed device	Multi 9: NG125 ComPact: NG160 ComPact: INS160 Multi 9: C120 Acti 9: iC120
[I _e] rated operational current	160 A
[I _n] rated current	160 A
Length	165 mm
Net weight	0.48 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	480 g
Package 1 Height	5 cm
Package 1 width	10 cm
Package 1 Length	20 cm
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Weight	5.1 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	50
Package 3 Weight	24 kg
Package 3 Height	75 cm

Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile