



Main

Range	Linergy
Range of product	Linergy
Product or component type	One-piece connection
Product name	Linergy BW
Product name	Prisma P enclosure Prisma G enclosure Linergy BW busbar
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy BW busbar
Poles description	4P
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 550 mm
Installed device	ComPact: INS160 Multi 9: NG125 with earth leakage protection ComPact: NG160 with earth leakage protection Multi 9: C120 with earth leakage protection Acti 9: iC120 with earth leakage protection
[Ie] rated operational current	160 A
[In] rated current	160 A
Length	440 mm
Net weight	1 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	957 g
Package 1 Height	4.3 cm
Package 1 width	7.8 cm
Package 1 Length	42.6 cm
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Weight	15.3 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	60
Package 3 Weight	73.3 kg
Package 3 Height	43 cm

---

Package 3 width	80 cm
Package 3 Length	120 cm

---

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>

---