



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection
Product name	Prisma P enclosure
Accessory / separate part category	Connection accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

## Complementary

Cubicle-device connection	Linergy busbar
Poles description	3P
Installation description	Cubicle - width 650 mm
Installed device	<p>ComPact: fixed INS250 - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed INS250 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed INV250 - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed INV250 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX100...160 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX250 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX100...160 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX250 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX100...160 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX250 without earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX100...160 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX250 without earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX100...160 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX250 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: drawout NSX100...160 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: drawout NSX250 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX100...160 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX250 with earth leakage protection - control: direct front rotary handle horizontal installation</p> <p>ComPact: plug-in NSX100...160 with earth leakage protection - control: motor mechanism horizontal installation</p> <p>ComPact: plug-in NSX250 with earth leakage protection - control: motor mechanism horizontal installation</p>
[I <sub>e</sub> ] rated operational current	250 A
[I <sub>n</sub> ] rated current	250 A
Busbar cross section	20 x 3 mm
Net weight	1.24 kg

Quantity per set	Set of 1
Functional unit	650 mm 400 mm Prisma P cubicle ComPact INS250 fixed direct front rotary handle horizontal 3P 1 direct 4 650 mm 400 mm Prisma P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 650 mm 400 mm Prisma P cubicle ComPact INS250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 650 mm 400 mm Prisma P cubicle ComPact INV250 fixed direct front rotary handle horizontal 3P 1 direct 4 650 mm 400 mm Prisma P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 1 Linergy FC 7 650 mm 400 mm Prisma P cubicle ComPact INV250 fixed direct front rotary handle vertical 3P 3 Linergy FC 7 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without plug-in direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without plug-in motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without drawout direct front rotary handle horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without drawout motor mechanism horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 without plug-in direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 without plug-in motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 without drawout direct front rotary handle horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX250 without drawout motor mechanism horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with plug-in direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with plug-in motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with drawout direct front rotary handle horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with drawout motor mechanism horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in direct front rotary handle horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in motor mechanism horizontal 3P 1 direct 3 650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout direct front rotary handle horizontal 3P 1 direct 5 650 mm 400 mm Prisma P cubicle ComPact NSX250 with drawout motor mechanism horizontal 3P 1 direct 5

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.24 kg
Package 1 Height	5 cm
Package 1 width	28 cm
Package 1 Length	39 cm
Unit Type of Package 2	P12
Number of Units in Package 2	45
Package 2 Weight	55.8 kg
Package 2 Height	80 cm

Package 2 width	80 cm
Package 2 Length	120 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>